



## CONTAINER CHASSIS MODEL: 40' MX

Fifth Wheel Height  
47 1/4"

Width  
96" (2.44 m)

Length  
40' 10" (12.45 m)

Capacity  
30,000 kg  
(66,138 lbs)

Tare Weight  
3640 kg  
(8,024 lbs)

### BODY

**Gooseneck:** H-beam fabricated, 1/2" x 4" thick flange and 1/4" thick web, in high resistance steel.

**Bolsters:** Front and rear bolsters in 1/4" thickness, in high resistance steel.

**Frame Structure:** Rolled I-beam, 12" x 4" reinforced, crossmembers fabricated channel type 3/16" and 1/4" thick", in high resistance steel.

**Bumper:** 1/4" thick in square tube, in high resistance steel. According with DOT.

**Landing Gear:** Landing gear support brackets are fabricated of 1/4" thickness, in high resistance steel, and Landing Gear JOST A440.

**Locks:** 2 Twist Locks and 2 Pin Locks. Brand: Buffer or TOCA.

**Pintle Hitch:** PH400 Holland /Premier.



## CONTAINER CHASSIS MODEL: 40' MX

### SUSPENSION

Pneumatic suspension on two axles.  
Meritor or HJ Rockwell.

**Axles:** 5" round axles with 30,000 lbs capacity 71-1/2" Track.

**Brakes:** 16-1/2" x 7" cast iron outboard mounted brake drums.

**ABS System:** Wabco 2S-1M

### RIMS AND TIRES

Radial Tires 11R22.5 16PLY

Steel Rims 8.25 X 22.5 Hub Piloted 5

**Mud Flaps:** 2 mud flaps 30" x 24 ", rubber material.

### FINISH

**Primer:** Sherwin-Williams, 70% Zinc, with thickness of 2 to 3 mills dry to 70 % solids.

**Top Coat:** Sherwin-Williams, Genesis GC 3.5 Low VOC Acrylic Polyurethane, with thickness of 2 to 2.5 mills dry.

### ELECTRICAL SYSTEM

**Harness:** Grote Sealed Harness.

**Gladhands:** Phillips.

**Wiring and lights:** Rear, central and front lights in optronics brand.  
12 Volt, 7 ways receptacle.



## OPCIONAL COMPONENTS

### AXLES

- Retractable
- Self-inflation
- Anti-roll

- GPS
- Aluminum Rims
- Odometer
- Paint color

### TIRES

- Firestone
- Goodyear
- Michelin