



CONTAINER CHASSIS MODEL: 53' GOOSENECK

Fifth Wheel Height
47 1/4"

Width
96" (2.44 m)

Length
53' 8" (16.36 m)

Capacity
30,500 kg
(67,200 lbs)

Tare Weight
3,526 kg
(7,773 lbs)

BODY

Gooseneck: H-beam fabricated, 5/8" x 4" thick flange and 5/16" thick web, in high resistance steel.

Bolsters: Front and rear bolsters in 1/4" thickness, in high resistance steel.

Frame Structure: Rolled I-beam, 12" x 4" reinforced, crossmembers fabricated channel type 3/16" and 1/4" thickness, in high resistance steel.

Bumper: 1/4" thick in square tube, in high resistance steel. According with DOT.

Landing Gear: Landing gear support brackets are fabricated of 1/4" thick, in high resistance steel, and Landing Gear JOST A440.

Locks: 2 Twist Locks and 2 Pin Locks, Buffer or Toca.



CONTAINER CHASSIS MODEL: 53' GOOSENECK

SUSPENSION

Equalized tandem mechanical suspension, overslung mounting, under mounting hangers with three leaf high arch spring. HUTCH

Axles: 5" round axles with 22,500 lbs capacity 71-1/2" track

Brakes: 16-1/2" x 7" cast iron outboard mounted

ABS System: Wabco 2S-1M

TIRES AND RIMS

Radial Tires, 11R22.5 16PLY

Steel Rims 8.25 x 22.5 Hub Piloted 5

Mud Flaps: 2 mud flaps 30" x 24 ", rubber material.



FINISH

Primer: Sherwin-Williams, 70% Zinc, with thickness of 2 to 3 mills dry. To 70 % solids.

Top coat: Sherwin-Williams, Genesis GC 3.5 Low VOC Acrylic Polyurethane, with thickness of 2 to 2.5 mills dry

ELECTRICAL SYSTEM

Harness: Phillips Sealed Harness.

Gladhands: Phillips.

Wiring and lights: Rear, central and front lights in brand optronics.
12 Volts, 7 ways receptacle.



OPCIONAL COMPONENTS

AXLES

- Self-inflation
- Anti-roll

- GPS
- Aluminum Rims
- Odometer
- Paint Color

TIRES

- Firestone
- Goodyear
- Michelin